

# Accessories for separable tee connectors

For FMCEAS-630, MSCEA/EC - 630/C

**formfit**

**elascon**  
EC

## Medium Voltage (MV) MV Separable connectors




### Insulating Plug **FMPI - 630/Z**

- Epoxy resin moulding which provides a dead-end facility for separable tee connector FMCEAUs-630/C.
- Operated when de-energized.
- Protected by a cap of semi-conducting EPDM.
- References : 12 kV - **FMPI - 630/Z - 12**  
24 kV - **FMPI - 630/Z - 24**  
36 kV - **FMPI - 630/Z - 36**
- Packing : per piece.



### Insulating Plug **FMP1-630/Z-TP**

- Epoxy resin moulding which provides a dead-end facility for separable tee connector FMCEAs-630/400.
- Includes a capacitive voltage divider that is protected by a cap of semi-conducting EPDM during normal use.
- References : 12 kV - **FMPI - 630/Z - 12 - TP**  
24 kV - **FMPI - 630/Z - 24 - TP**  
36 kV - **FMPI - 630/Z - 36 - TP**
- Packing : per piece



### Straight Connecting Plug **FMPCs-630-C/Z**

- Epoxy resin moulded over a copper rod. For connecting one separable tee connector FMCTs-400 with one separable tee connector FMCEAs-630/400 or FMCEAUs-630/C in combinations such as disconnectable joint, tee off joint or dual cable supply.
- Connection to rod by the clamping screws of the connectors. Integral reconstitution of insulation. For combination FMCTs-400 with FMCEAs-630/400 : protection through screen continuity.
- Operated when de-energized.
- References : 12 kV - **FMPCs - 630 C/Z - 12**  
24 kV - **FMPCs - 630 C/Z - 24**
- Packing : per piece.



### Test Rod **FMTR - 400/630**

- For testing or earthing of cables equipped With separable tee connectors.
- Screwed onto clamping screw of tee connectors.
- Reference : 12 kV and 24 kV- **FMTR - 400/630**
- Packing : per piece.